

# PERFORMANCE SPECIFICATIONS

Model	Heating Efficiency AFUE	Input Btuh Capacity [kW]	Output Btuh Capacity [kW]	Tons of Add-on Cooling [kW]	Dimensions: HxWxD [inches]
<b>SLP98V</b>					
SLP98UH070XV36B	97.0%	66,000 (19.3)	64,000 (18.7)	2-3 (7.0-10.6)	33 x 17-1/2 x 27-3/4
SLP98UH090XV36C	98.0%	88,000 (25.8)	85,000 (24.9)	2-3.5 (7.0-12.3)	33 x 21 x 27-3/4
SLP98UH090XV48C	97.5%	88,000 (25.8)	85,000 (24.9)	2.5-4 (8.8-14.0)	33 x 21 x 27-3/4
SLP98UH090XV60C	98.2%	88,000 (25.8)	85,000 (24.9)	3-5 (10.6-17.6)	33 x 21 x 27-3/4
SLP98UH110XV60C	97.5%	110,000 (32.2)	106,000 (31.0)	3-5 (10.6-17.6)	33 x 21 x 27-3/4
SLP98UH135XV60D	97.5%	132,000 (38.7)	128,000 (37.5)	3.5-5 (12.3-17.6)	33 x 24-1/2 x 27-3/4
SLP98DF070XV36B	97.5%	66,000 (19.3)	64,000 (18.7)	2-3 (7.0-10.6)	33 x 17-1/2 x 27-3/4
SLP98DF090XV36C	97.5%	88,000 (25.8)	84,000 (24.6)	2-3 (7.0-10.6)	33 x 21 x 27-3/4
SLP98DF090XV48C	97.5%	88,000 (25.8)	85,000 (24.9)	3-4 (10.6-14.0)	33 x 21 x 27-3/4
SLP98DF090XV60C	97.5%	88,000 (25.8)	85,000 (24.9)	3-5 (10.6-17.6)	33 x 21 x 27-3/4
SLP98DF110XV60C	98.2%	110,000 (32.2)	107,000 (31.3)	3.5-5 (12.3-17.6)	33 x 21 x 27-3/4
<b>G61MPV</b>					
G61MPV-36B-045	94.1%	44,000 (12.9)	39,000 (11.4)	2-3 (7.0-10.6)	40 x 17-1/2 x 28-1/2
G61MPV-36B-070	94.1%	66,000 (19.3)	61,000 (17.9)	2-3.5 (7.0-12.3)	40 x 17-1/2 x 28-1/2
G61MPV-36B-071	95.0%	66,000 (19.3)	62,000 (18.2)	2-3.5 (7.0-12.3)	40 x 17-1/2 x 28-1/2
G61MPV-36C-090	94.3%	88,000 (25.8)	79,000 (23.1)	2-3.5 (7.0-12.3)	40 x 21 x 28-1/2
G61MPV-60C-090	94.6%	88,000 (25.8)	82,000 (24.0)	3.5-5 (12.3-17.6)	40 x 21 x 28-1/2
G61MPV-60C-091	95.0%	88,000 (25.8)	84,000 (24.6)	3.5-5 (12.3-17.6)	40 x 21 x 28-1/2
G61MPV-60C-110	94.3%	110,000 (32.2)	99,000 (29.0)	3.5-5 (12.3-17.6)	40 x 21 x 28-1/2
G61MPV-60C-111	95.0%	110,000 (32.2)	103,000 (30.2)	3.5-5 (12.3-17.6)	40 x 21 x 28-1/2
G61MPV-60D-135	94.6%	132,000 (38.7)	122,000 (35.7)	3.5-5 (12.3-17.6)	40 x 24-1/2 x 28-1/2
<b>G60</b>					
G60DF-36A-070X	80.0%	66,000 (19.3)	54,000 (15.8)	2-3 (7.0-10.6)	40 x 14-1/2 x 28-1/2
G60DF-36B-090	80.0%	88,000 (25.8)	72,000 (21.1)	2-3 (7.0-10.6)	40 x 17-1/2 x 28-1/2
G60DF-48C-110	80.0%	110,000 (32.2)	90,000 (26.4)	2.5-4 (8.8-14.1)	40 x 21 x 28-1/2
G60UH-24A-070	80.0%	66,000 (19.3)	54,000 (15.8)	1.5-2 (5.3-7.0)	40 x 14-1/2 x 28-1/2
G60UH-36A-070X	80.0%	66,000 (19.3)	54,000 (15.8)	1.5-3 (5.3-10.6)	40 x 14-1/2 x 28-1/2
G60UH-36B-090	80.0%	88,000 (25.8)	72,000 (21.1)	2-3 (7.0-10.6)	40 x 17-1/2 x 28-1/2
G60UH-36C-110	80.0%	110,000 (32.2)	89,000 (26.1)	2-3 (7.0-10.6)	40 x 21 x 28-1/2
G60UH-48B-090X	80.0%	88,000 (25.8)	72,000 (21.1)	3-4 (10.6-14.1)	40 x 17-1/2 x 28-1/2
G60UH-60C-110X	80.0%	110,000 (32.2)	90,000 (26.4)	4-5 (14.0-17.6)	40 x 21 x 28-1/2
G60UH-60D-135	80.0%	132,000 (38.7)	108,000 (31.6)	4-5 (14.0-17.6)	40 x 24-1/2 x 28-1/2
<b>EL195E</b>					
EL195UH045XE36B	95.0%	44,000 (12.9)	42,000 (12.3)	1.5-3 (5.3-10.6)	33 x 17-1/2 x 27-3/4
EL195UH070XE36B	95.0%	66,000 (19.3)	63,000 (18.5)	1.5-3 (5.3-10.6)	33 x 17-1/2 x 27-3/4
EL195UH090XE48C	95.0%	88,000 (25.8)	84,000 (24.6)	2.5-4 (8.8-14.0)	33 x 21 x 27-3/4
EL195UH110XE60C	95.0%	110,000 (32.2)	105,000 (30.8)	3-5 (10.6-17.6)	33 x 21 x 27-3/4
EL195UH135XE60D	95.0%	132,000 (38.7)	126,000 (36.9)	3.5-5 (12.3-17.6)	33 x 24-1/2 x 27-3/4
EL195DF045XE36B	95.0%	44,000 (12.9)	42,000 (12.3)	1.5-3 (5.3-10.6)	33 x 17-1/2 x 27-3/4
EL195DF070XE48B	95.0%	66,000 (19.3)	64,000 (18.7)	2-4 (7.0-14.0)	33 x 17-1/2 x 27-3/4
EL195DF090XE48C	95.0%	88,000 (25.8)	85,000 (24.9)	2-4 (7.0-14.0)	33 x 21 x 27-3/4
EL195DF110XE60C	95.0%	110,000 (32.2)	106,000 (31.0)	3-5 (10.6-17.6)	33 x 21 x 27-3/4

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change without notice.

# PERFORMANCE SPECIFICATIONS

Model	Heating Efficiency AFUE	Input Btuh Capacity [kW]	Output Btuh Capacity [kW]	Tons of Add-on Cooling [kW]	Dimensions: HxWxD [inches]
<b>G50</b>					
G50DF-24A-045X	80.0%	44,000 (12.9)	36,000 (10.5)	1.5-2 (5.3-7.0)	40 x 14-1/2 x 28-1/2
G50DF-36A-070X	80.0%	66,000 (19.3)	53,000 (15.5)	2-3 (7.0-10.6)	40 x 14-1/2 x 28-1/2
G50DF-36B-090	80.0%	88,000 (25.8)	71,000 (20.8)	2-3 (7.0-10.6)	40 x 17-1/2 x 28-1/2
G50DF-48C-090X	80.0%	88,000 (25.8)	71,000 (20.8)	3-4 (10.6-14.1)	40 x 21 x 28-1/2
G50DF-48C-110	80.0%	110,000 (32.2)	89,000 (26.1)	2-4 (7.0-14.1)	40 x 21 x 28-1/2
G50DF-60C-110	80.0%	110,000 (32.2)	90,000 (26.4)	4-5 (14.1-17.6)	40 x 21 x 28-1/2
G50DF-60D-135	80.0%	132,000 (38.7)	108,000 (31.7)	4-5 (14.1-17.6)	40 x 24-1/2 x 28-1/2
G50UH-24A-045X	80.0%	44,000 (12.9)	35,000 (10.2)	1.5-2 (5.3-7.0)	40 x 14-1/2 x 28-1/2
G50UH-24A-070	80.0%	66,000 (19.3)	53,000 (15.5)	1.5-2.5 (5.3-8.8)	40 x 14-1/2 x 28-1/2
G50UH-36A-070X	80.0%	66,000 (19.3)	53,000 (15.5)	2-3 (7.0-10.6)	40 x 14-1/2 x 28-1/2
G50UH-36B-090	80.0%	88,000 (25.8)	71,000 (20.8)	2-3 (7.0-10.6)	40 x 17-1/2 x 28-1/2
G50UH-36C-110	80.0%	110,000 (32.2)	88,000 (25.8)	2-3 (7.0-10.6)	40 x 21 x 28-1/2
G50UH-48B-090X	80.0%	88,000 (25.8)	71,000 (20.8)	3-4 (10.6-14.1)	40 x 17-1/2 x 28-1/2
G50UH-48C-110	80.0%	110,000 (32.2)	87,000 (25.5)	3-4 (10.6-14.1)	40 x 21 x 28-1/2
G50UH-48C-135	80.0%	132,000 (38.7)	106,000 (31.0)	2-4 (7.0-14.1)	40 x 21 x 28-1/2
G50UH-60C-110	80.0%	110,000 (32.2)	88,000 (25.8)	4-5 (14.0-17.6)	40 x 21 x 28-1/2
G50UH-60D-135	80.0%	132,000 (38.7)	107,000 (31.3)	4-5 (14.0-17.6)	40 x 24-1/2 x 28-1/2
G50UH-60D-155	80.0%	154,000 (45.1)	122,000 (35.7)	4-5 (14.0-17.6)	40 x 24-1/2 x 28-1/2
<b>ML193</b>					
ML193DF045P36B	93.0%	44,000 (12.9)	41,000 (12.0)	2.5-3 (8.8-10.6)	33 x 17-1/2 x 27-3/4
ML193DF070P36B	93.0%	66,000 (19.3)	61,000 (17.9)	2.5-3 (8.8-10.6)	33 x 17-1/2 x 27-3/4
ML193DF090P48C	93.0 %	88,000 (25.8)	82,000 (24.0)	3-4 (10.6-14.0)	33 x 21 x 27-3/4
ML193DF110P60C	93.0%	110,000 (32.2)	102,000 (29.9)	4-5 (14.0-17.5)	33 x 21 x 27-3/4
ML193UH045P24B	93.0%	44,000 (12.9)	41,000 (12.0)	1.5-2 (5.3-7.0)	33 x 17-1/2 x 27-3/4
ML193UH045P36B	93.0%	44,000 (12.9)	42,000 (12.3)	2.5-3 (8.8-10.6)	33 x 17-1/2 x 27-3/4
ML193UH070P24B	93.0%	66,000 (19.3)	62,000 (18.2)	1.5-2 (5.3-7.0)	33 x 17-1/2 x 27-3/4
ML193UH070P36B	93.0%	66,000 (19.3)	62,000 (18.2)	2.5-3 (8.8-10.6)	33 x 17-1/2 x 27-3/4
ML193UH090P36C	93.0%	88,000 (25.8)	83,000 (24.3)	2-3 (7.0-10.6)	33 x 21 x 27-3/4
ML193UH090P48C	93.0%	88,000 (25.8)	83,000 (24.3)	3-4 (10.6-14.0)	33 x 21 x 27-3/4
ML193UH110P48C	93.0%	110,000 (32.2)	104,000 (30.5)	3-4 (10.6-14.0)	33 x 21 x 27-3/4
ML193UH110P60C	93.0%	110,000 (32.2)	104,000 (30.5)	4-5 (14.0-17.5)	33 x 21 x 27-3/4
ML193UH135P60D	93.0%	132,000 (38.7)	124,000 (36.3)	4-5 (14.0-17.5)	33 x 24-1/2 x 27-3/4
<b>ML180E</b>					
ML180UH045E36A	80.0%	44,000 (12.9)	36,000 (10.5)	1.5-3 (5.3-10.6)	33 x 14-1/2 x 27-3/4
ML180UH045XE36A	80.0%	44,000 (12.9)	36,000 (10.5)	1.5-3 (5.3-10.6)	33 x 14-1/2 x 27-3/4
ML180UH070E36B	80.0%	66,000 (19.3)	53,000 (15.5)	1.5-3 (5.3-10.6)	33 x 17-1/2 x 27-3/4
ML180UH070XE36B	80.0%	66,000 (19.3)	53,000 (15.5)	1.5-3 (5.3-10.6)	33 x 17-1/2 x 27-3/4
ML180UH090E48B	80.0%	88,000 (25.8)	72,000 (21.1)	2.5-4 (8.8-14.0)	33 x 17-1/2 x 27-3/4
ML180UH090XE48B	80.0%	88,000 (25.8)	72,000 (21.1)	2.5-4 (8.8-14.0)	33 x 21 x 27-3/4
ML180UH090E60C	80.0%	88,000 (25.8)	72,000 (21.1)	3-5 (10.6-17.6)	33 x 21 x 27-3/4
ML180UH110E60C	80.0%	110,000 (32.2)	90,000 (26.4)	3-5 (10.6-17.6)	33 x 21 x 27-3/4
ML180UH110XE60C	80.0%	110,000 (32.2)	90,000 (26.4)	3-5 (10.6-17.6)	33 x 21 x 27-3/4
ML180UH135E60D	80.0%	132,000 (38.7)	107,000 (31.3)	3.5-5 (12.3-17.6)	33 x 24-1/2 x 27-3/4
ML180DF045E36A	80.0%	44,000 (12.9)	36,000 (10.5)	1.5-3 (5.3-10.6)	33 x 14-1/2 x 27-3/4
ML180DF070E36B	80.0%	66,000 (19.3)	54,000 (15.8)	1.5-3 (5.3-10.6)	33 x 17-1/2 x 27-3/4
ML180DF090XE48B	80.0%	88,000 (25.8)	72,000 (21.1)	2.5-4 (8.8-14.0)	33 x 17-1/2 x 27-3/4
ML180DF110XE60C	80.0%	110,000 (32.2)	90,000 (26.4)	3-5 (10.6-17.6)	33 x 21 x 27-3/4

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change without notice.  
 Low-NOx units (labeled "X" in the model number) meet California Nitrogen Oxides standards.