

LANDMARK® ROOFTOP UNIT PERFORMANCE SPECIFICATIONS

		COOLING DATA		HEATING INPUT				PHYSICAL DATA			
Nom. Ton	Model	EER	SEER or IEER	Low	Standard	Medium	High	Dimensions H x W x L [inches]	Ship Wt. [lbs.]		
										KW Range*	
GAS/ELECTRIC UNITS	2	KGA024S4D	11.4	13.0	—	65,000	—	—	39 x 47 x 86	591	
	2.5	KGA030S4D	11.2	13.0	—	65,000	—	—	39 x 47 x 86	593	
	3	KGA036S4B	10.7	13.0	—	65,000	105,000	—	39 x 47 x 86	594	
	4	KGA048S4B	11.0	13.0	—	65,000	105,000	150,000	39 x 47 x 86	631	
	5	KGA060S4B	11.2	13.0	—	65,000	105,000	150,000	39 x 47 x 86	661	
	6	KGA072S4B	11.0	11.2	—	65,000	105,000	150,000	47 x 47 x 86	760	
	7.5	KGA090S4B	11.0	11.2	—	—	105,000	150,000	47 x 47 x 99	865	
	7.5	KGA092S4B	11.0	11.2	—	130,000	180,000	240,000	47 x 61 x 102	1,052	
	8.5	KGA102S4B	11.0	11.2	—	130,000	180,000	240,000	47 x 61 x 102	1,072	
	10	KGA120S4B	11.0	11.2	—	130,000	180,000	240,000	47 x 61 x 102	1,112	
	12.5	KGA150S4B	10.8	11.0	—	130,000	180,000	240,000	47 x 61 x 102	1,202	
	15	KGA180S4B	10.8	11.0	—	260,000	360,000	480,000	55 x 92 x 108	2,055	
	17.5	KGA210S4B	10.8	11.0	—	260,000	360,000	480,000	55 x 92 x 108	2,200	
	20	KGA240S4B	10.8	11.0	—	260,000	360,000	480,000	55 x 92 x 133	2,295	
25	KGA300S4B	10.0	9.9	—	260,000	360,000	480,000	55 x 92 x 133	2,375		
				KW Range*							
ELECTRIC/ELECTRIC UNITS	2	KCA024S4D	11.4	13.0	7.5	10.0	—	—	39 x 47 x 86	555	
	2.5	KCA030S4D	11.2	13.0	7.5	10.0	—	—	39 x 47 x 86	557	
	3	KCA036S4B	10.7	13.0	7.5	15.0	—	—	39 x 47 x 86	558	
	4	KCA048S4B	11.0	13.0	7.5	15.0	—	—	39 x 47 x 86	595	
	5	KCA060S4B	11.2	13.0	7.5	15.0	22.5	—	39 x 47 x 86	625	
	6	KCA072S4B	11.2	11.4	7.5	15.0	22.5	30.0	47 x 47 x 86	724	
	7.5	KCA090S4B	11.2	11.4	7.5	15.0	22.5	30.0	47 x 47 x 99	827	
	7.5	KCA092S4B	11.2	11.4	7.5	15.0	22.5	30.0	45.0	47 x 61 x 102	1,052
	8.5	KCA102S4B	11.2	11.4	7.5	15.0	22.5	30.0	45.0	47 x 61 x 102	1,072
	10	KCA120S4B	11.2	11.4	15.0	22.5	30.0	45.0	60.0	47 x 61 x 102	1,112
	12.5	KCA150S4B	11.0	11.2	15.0	23.0	30.0	45.0	60.0	47 x 61 x 102	1,202
	15	KCA180S4B	11.0	11.2	15.0	30.0	45.0	60.0	—	55 x 92 x 108	2,000
	17.5	KCA210S4B	11.0	11.2	15.0	30.0	45.0	60.0	90.0	55 x 92 x 108	2,145
	20	KCA240S4B	11.0	11.2	15.0	30.0	45.0	60.0	90.0	55 x 92 x 133	2,240
25	KCA300S4B	10.0	10.1	15.0	30.0	45.0	60.0	90.0	55 x 92 x 133	2,320	
				47 Cap.	HSPF/ COP 47	17 Cap.	COP 17				
HEAT PUMPS	2	KHA024S4D	11.2	13.0	24,000	3.4	14,400	2.3	39 x 47 x 86	591	
	2.5	KHA030S4D	11.3	13.0	29,200	3.5	17,600	2.3	39 x 47 x 86	593	
	3	KHA036S4B	10.9	13.0	36,400	3.6	22,000	2.3	39 x 47 x 86	595	
	4	KHA048S4B	10.7	13.0	48,000	3.5	29,500	2.4	39 x 47 x 86	617	
	5	KHA060S4B	10.9	13.0	60,500	3.6	36,000	2.4	47 x 47 x 86	727	
	6	KHA072S4B	11.0	11.2	70,000	3.3	40,000	2.25	47 x 47 x 99	810	
	7.5	KHA092S4B	11.0	11.2	89,000	3.3	53,000	2.25	47 x 61 x 102	1,114	
	8.5	KHA102S4B	11.0	11.2	100,000	3.3	55,000	2.25	47 x 61 x 102	1,146	
	10	KHA120S4B	11.0	11.2	116,000	3.3	72,000	2.25	47 x 61 x 102	1,212	
	12.5	KHA150S4B	10.6	10.7	138,000	3.3	82,000	2.05	47 x 61 x 124	1,412	
15	KHA180S4B	10.6	10.7	178,000	3.2	104,000	2.05	55 x 92 x 130	2,100		
20	KHA240S4B	10.6	10.7	220,000	3.2	128,000	2.05	55 x 92 x 130	2,250		

Certified in accordance with the USE certification program which is based on ARI Standard 210/240: 95°F outdoor air temperature and 80°F dB/67°F wb entering evaporator coil air.
 Certified in accordance with the ULE certification program which is based on ARI standard 340/360: 95°F outdoor air temperature and 80°F dB/67°F wb entering evaporator air; minimum external duct static pressure.
 Direct-drive blower motors available for 2- to 5-ton models.

*Nominal electric heat capacities are rated at 240V, 480V and 600V.
 **Heating CFM for gas models varies dependent upon heat option selected. Minimum Heating CFM for Heat Pumps does not include supplemental electric heat.
 Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change.