

T-CLASS™ AC/HP PERFORMANCE SPECIFICATIONS

			COOLING DATA ^{2, 3}			HEATING DATA ⁴			PHYSICAL DATA		
Nominal Tonnage		Model	Sound Rating dB ¹	ARI Rated Cap. [Btuh]	Efficiency [SEER] ⁵	Efficiency [EER]	Efficiency [HSPF] ⁶	Capacity [Btuh]	COP	Dimensions H x W x L [inches]	Ship. Wt. [lbs.]
AIR CONDITIONERS	3	TSA036S4	76	35,800	14.5	12.0	—	—	—	29.25 x 24.25 x 24.25	135
	3.5	TSA042S4	80	41,500	13.8	11.6	—	—	—	29.25 x 28.25 x 28.25	178
	4	TSA048S4	80	48,500	14.0	11.6	—	—	—	37.25 x 28.25 x 28.25	194
	5	TSA060S4	80	64,000	14.0	11.6	—	—	—	33.25 x 32.25 x 32.25	218
HEAT PUMPS	3	TPA036S4	76	35,000	14.0	11.7	8.2	34,200	3.64	33.25 x 24.25 x 24.25	180
	3.5	TPA042S4	80	44,000	13.5	11.5	8.7	40,500	3.74	33.25 x 28.25 x 28.25	220
	4	TPA048S4	80	43,500	13.5	11.5	8.2	43,500	3.36	37 x 28.25 x 28.25	250
	5	TPA060S4	80	59,000	13.0	11.0	8.0	54,000	3.24	43.25 x 28.25 x 28.25	255

T-CLASS HIGH-EFFICIENCY AC/HP PERFORMANCE SPECIFICATIONS

			COOLING DATA ^{2, 3}			HEATING DATA ⁴			PHYSICAL DATA		
Nominal Tonnage		Model	Sound Rating dB ¹	ARI Rated Cap. [Btuh]	Efficiency [SEER] ⁷	Efficiency [EER]	Efficiency [HSPF] ⁸	Capacity [Btuh]	COP	Dimensions H x W x L [inches]	Ship. Wt. [lbs.]
AIR CONDITIONERS	3	TSA036H4	76	38,000	16.0	13.2	—	—	—	37.25 x 28.25 x 28.25	164
	3.5	TSA042H4	78	41,500	15.0	12.7	—	—	—	29.25 x 28.25 x 28.25	198
	4	TSA048H4	78	49,000	14.7	12.2	—	—	—	37.25 x 28.25 x 28.25	221
	5	TSA060H4	80	56,000	14.5	12.0	—	—	—	33.25 x 32.25 x 32.25	238
HEAT PUMPS	3	TPA036H4	79	35,000	15.7	13.2	9.0	31,800	3.72	29.25 x 32.25 x 32.25	212
	3.5	TPA042H4	79	43,000	15.0	13.0	9.5	42,000	3.92	37 x 32.25 x 32.25	257
	4	TPA048H4	80	50,500	15.2	13.0	9.2	47,000	3.66	37 x 32.25 x 32.25	262
	5	TPA060H4	80	59,500	15.0	12.5	9.0	57,000	3.50	43.25 x 32.25 x 32.25	307

¹Sound rating number in accordance with test conditions included in ARI Standard 270.

²5-ton-and-under equipment certified in accordance with ULE certification program, which is based on ARI Standard 210/240.

³Cooling ratings, 95°F (35°C) outdoor air temperature and 80°F (27°C) db/67°F (19°C) wb entering indoor coil air.

⁴High-temperature heating ratings, 47°F (8°C) db/43°F (6°C) wb outdoor air temperature and 70°F (21°C) entering indoor coil air.

⁵Up to 14.5 SEER when the T-Class TSA036S4 split system is matched with the CH33-43 and SLP98UH110V60C furnace.

⁶Up to 8.7 HSPF when the T-Class TPA042S4 split system is matched with the CR33-50/60 and EL195DF110XE60C furnace.

⁷Up to 16.0 SEER when the T-Class TSA036H4 split system is matched with the C33-43 and ML180UH110E60C furnace.

⁸Up to 9.5 HSPF when the T-Class TPA042H4 split system is matched with the CX34-62C and SLP98UH110V60C furnace.

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change.