

Job: Location: Schedule No.:

SUBMITTAL DATA - **DUCTED MMD**A018S4-1P

MULTI-ZONE MINI-SPLIT HEAT PUMP

Engineer:
Architect:
Date:
For: Reference DAnnroval DReview DConstruction

FEATURES

• Pre Heat Function

System Designation:

- Low Charge Detection
- Auto Restart
 Built-In Condensate Pump
- Flare Connections
- Refrigerant R-410A
- Three Speed Fan
- · Wired Controller included

Product Warranty

All covered components - Twelve year limited warranty. Product registration required.

Product registration required.		
SPECIFICATIONS		
PERFORMANCE		
Cooling Capacity ¹ (Btu/h)		16,000
Heating Capacity ¹ (Btu/h)		18,000
Airflow (CFM)	High	485
	Medium	380
	Low	320
External Static Pressure (in. w.g.)		
Sound Pressure (dBA)	High	35
	Medium	33
	Low	31
ELECTRICAL DATA		
Power Supply (V/Hz/Φ)		208-230/60/1
Power Supply (V/Hz/Φ) Rated load amps (RLA)		208-230/60/1 1.5
Rated load amps (RLA)		1.5
Rated load amps (RLA) Power Output (W)	Height	1.5
Rated load amps (RLA) Power Output (W) DIMENSIONS	Height Width	1.5 90
Rated load amps (RLA) Power Output (W) DIMENSIONS	•	1.5 90 8-1/4
Rated load amps (RLA) Power Output (W) DIMENSIONS	Width	1.5 90 8-1/4 39-3/4
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in)	Width	1.5 90 8-1/4 39-3/4 25
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in)	Width Depth	1.5 90 8-1/4 39-3/4 25 1/4
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in)	Width Depth	1.5 90 8-1/4 39-3/4 25 1/4 1/2
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in) Condensate drain connection	Width Depth	1.5 90 8-1/4 39-3/4 25 1/4 1/2



OPTIONAL ACCESSORIES Non-Programmable Controller (M0STAT61Q-1): 1+ Wireless Remote Controller (M0STAT60Q-1): Programmable Controller (M0STAT64Q-1):

NOTES

Cooling and Heating capacity data is rated at the following conditions:

Cooling: 80°FDB / 67°FWB Indoor, 95°FDB Outdoor Heating: 70°FDB Indoor, 47°FDB / 43°FWB Outdoor











SUBMITTAL DATA – **DUCTED MMDA018**S4-1P **MULTI-ZONE MINI-SPLIT** HEAT PUMP

DIMENSIONAL DRAWINGS - INCHES (MM)

