

SUBMITTAL DATA - INDOOR UNIT VOWA015H4-3P VRF Heat Pump & Heat Recovery

One West Ocean 445 Indian IInit	For: Reference Approval Review Construction		
System Designation:	Date:		
Schedule No.:	Location:		
Location:	Architect:		
Job:	Engineer:		

One Way Cassette Indoor Unit

FEATURES

- Pre Heat Function Integral Condensate Pump
- Auto Addressing
 Electronic Expansion Valve
- Auto Restart
 Built-in Four Dry Contact Relays
- Flare Connections
- Refrigerant R-410A
- High-Efficiency DC Motor Six capacity sizes from 7,000 to 24,000 Btu/h

WARRANTY

• 10-year limited warranty.*See warranty for details.

SPECIFICATIONS		
PERFORMANCE		
Cooling Capacity1 (Btu/h)		15000
Heating Capacity1 (Btu/h)		17000
Airflow (CFM)	High	379
	Medium	345
	Low	309
External Static Pressure (in.w.g.)		0~0.04
Sound (dBA)	High	40.7
•	Medium	38.1
	Low	36.3

ELECTRICAL DATA	
Power Supply (Volts/Phase/Hertz)	208/230V-1Ph-60Hz
Minimum Circuit Ampacity (MCA)	0.44
Max. Overcurrent Protection (MOCP)	15
Cooling Power Input ² (W)	23
Cooling Rated Current (A)	0.3
Heating Power Input ² (W)	18
Heating Rated Current (A)	0.3
Indoor Fan Motor Input (W)	20(H:0PA)

DIMENSIONS		
Unit Dimensions (in)	Height	7-1/2
	Width	50-1/4
	Depth	17-3/4
Diffuser Panel Dimensions (in)	Height	1
	Width	53-1/8
	Depth	19-7/8
Liquid Pipe Connection (in)		1/4
Gas Pipe Connection (in)		1/2
Drain Connection (in)		1
Net Weight (lb)		36.8
Shipping Weight (lb)		49.6



OPTIONAL ACCESSORIES	
Non-Programmable Controller	V0STAT54P-3
Programmable Wired Controller	V0STAT51P-3
Infrared Wireless Controller	V0STAT52P-1
Occupancy Sensor	V0SNSR78P-3
HHE Relay Kit	V0CTRL92P-3
Hotel Keycard Interface	V0CTRL88P-1

NOTES

- Cooling and Heating capacity data is rated at the following conditions: Cooling: 80°FDB / 67°FWB Indoor, 95°FDB
 Outdoor Heating: 70°FDB Indoor, 47°FDB / 43°FWB Outdoor.
- 2. Power Input values are rated at high fan speed.







SUBMITTAL DATA - INDOOR UNIT VOWA015H4-3P

VRF Heat Pump & Heat Recovery

DIMENSIONAL DRAWINGS - INCHES (MM)

