

SUBMITTAL DATA - CEILING/FLOOR

MCFA024S4-1P

MULTI-ZONE MINI-SPLIT HEAT PUMP

Job:	Engineer:	
Location:	Architect:	
Schedule No.:	Date:	
System Designation:	For: □Reference □Approval □Review □Construction	

FEATURES

- Pre Heat Function
- Auto Restart

- Flare Connections
- LED Readout Panel
- Refrigerant R-410A
- · Wireless Remote Controller included

Product Warranty

All covered components - Twelve year limited warranty. Product registration required.

Product registration required.			
SPECIFICATIONS			
PERFORMANCE			
Cooling Capacity ¹ (Btu/h)		23,000	
Heating Capacity ¹ (Btu/h)		25,000	
Airflow (CFM)	High	880	
	Medium	770	
	Low	650	
External Static Pressure (in. w.g.)			
Sound Pressure (dBA)	High	58.5	
	Medium	55	
	Low	52	
ELECTRICAL DATA			
Power Supply (V/Hz/Φ)		208-230/60/1	
Power Supply (V/Hz/Φ) Rated load amps (RLA)		208-230/60/1 1.5	
Rated load amps (RLA)		1.5	
Rated load amps (RLA) Power Output (W)	Height	1.5	
Rated load amps (RLA) Power Output (W) DIMENSIONS	Height Width	1.5 55	
Rated load amps (RLA) Power Output (W) DIMENSIONS	•	1.5 55 9-1/4	
Rated load amps (RLA) Power Output (W) DIMENSIONS	Width	1.5 55 9-1/4 42-1/8	
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in)	Width	1.5 55 9-1/4 42-1/8 26-5/8	
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in)	Width Depth	1.5 55 9-1/4 42-1/8 26-5/8 3/8	
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in) Condensate drain connection Unit Shipping Weight (lb)	Width Depth	1.5 55 9-1/4 42-1/8 26-5/8 3/8 5/8	
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in) Condensate drain connection	Width Depth	1.5 55 9-1/4 42-1/8 26-5/8 3/8 5/8	



OPTIONAL ACCESSORIES	
Non-Programmable Controller (M0STAT61Q-1):	
Wireless Remote Controller (M0STAT60Q-1):	1+
Programmable Controller (M0STAT64Q-1):	

NOTES

1. Cooling and Heating capacity data is rated at the following conditions:

Cooling: 80°FDB / 67°FWB Indoor, 95°FDB Outdoor Heating: 70°FDB Indoor, 47°FDB / 43°FWB Outdoor














SUBMITTAL DATA - CEILING/FLOOR MCFA024S4-1P

MULTI-ZONE MINI-SPLIT HEAT PUMP

DIMENSIONAL DRAWINGS - INCHES (MM)







BOTTOM VIEW