

SUBMITTAL DATA - WALL MOUNTED MHB018S4S-1P - MWHB018S4-2P

SINGLE ZONE MINI-SPLIT HEAT PUMP

| Job: | Engineer: | | |
|---------------------|---|--|--|
| Location: | Architect: | | |
| Schedule No.: | Date: | | |
| System Designation: | For: ☐ Reference ☐ Approval ☐ Review ☐ Construction | | |

FEATURES

Outdoor Unit: MHB018S4S-1P



- **DC Inverter Control**
- **Compressor Overcurrent Protection**
- **Defrost Control**

Indoor Unit: MWHB018S4-2P



- **Pre-Heat Function**
- **Auto Restart**
- Three Speed Fan
- **Flare Connections**
- **Multi-Refrigerant Outlet**
- **LED Readout**
- Wireless Remote Included

| PIPING | |
|--|---------|
| Line Set and Elevation Guidelines | |
| Maximum Line Set Length ft. (m) | 98 (30) |
| Maximum Elevation - Outdoor Unit Below/Above Indoor Unit ft. (m) | 66 (20) |
| Liquid Line Set Diameter (in.) | 1/4 |
| Gas Line Set Diameter (in.) | 1/2 |
| Pre-Charged (ft.) | 25 |
| Additional Charge Per Ft. (oz.) | 0.16 |

PRODUCT WARRANTY

Compressor - Seven year limited warranty All other covered components - Five year limited warranty





OPTIONAL ACCESSORIES

Non-Programmable Controller (M0STAT61Q-1)

Non-Programmable Controller (M0STAT120L-1)

Programmable Controller (M0STAT120N-1)

Hail Guard Set (M9GARD20Q-1/24M82)



NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings, and Dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.




SUBMITTAL DATA - WALL MOUNTED MHB018S4S-1P - MWHB018S4-2P


SINGLE ZONE MINI-SPLIT HEAT PUMP


| OUTDOOR SPECIFICATIONS | | | | | |
|---------------------------------------|--------------|---|--------|---------------|--|
| PERFORMANCE | | GENERAL DATA | | | |
| Cooling Capacity (Btu/h) ¹ | 18,000 | Connection Ratio (%) | | 100% | |
| EER2 | 11.0 | Max. # of Indoor Units | | 1 unit | |
| SEER2 | 19.5 | Sound Data (dBA) | | 57 | |
| Heating Capacity (Btu/h) ¹ | 18,800 | Refrigerant type | | R-410A | |
| HSPF2 | 8.7 | Factory refrigerant charge | 2 | 2 lbs. 16 oz. | |
| Outdoor Fan Total Air Volume (CFM) | 1,235 | DIMENSIONS | | | |
| Ambient Temperature Operating Range | | Unit Dimensions (in) | Height | 21-7/8 | |
| Cooling | 5°F - 122°F | | Width | 32-1/8 | |
| Heating | 5°F - 86°F | | Depth | 12-1/2 | |
| ELECTRICAL DATA | | Shipping Weight (lb) | | 80 | |
| Power Supply (V/Hz/Φ) | 208/230/60/1 | Net Weight (lb) | | 74 | |
| Minimum Circuit Ampacity (A) | 15 | NOTES | | | |
| Maximum Overcurrent Protection (A) | 20 | | | | |
| Outdoor Fan Motor RLA (A) | 0.4 | Cooling and Heating Capacity data is rated at the following conditions: | | | |
| No. of Compressors | 1 | conditions: Cooling: 80°FDB / 67°FWB Indoor, 95°FDB Outdoor | | | |
| | | Heating: 70°FDB Indoor, 47°FDB / 43 | | | |

OUTDOOR DIMENSIONAL DRAWINGS - INCHES (MM)



TOP VIEW





FRONT VIEW

NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings, and Dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

496053 (202312)

©2023 Lennox Industries, Inc.



SUBMITTAL DATA - WALL-MOUNTED MHB018S4S-1P - MWHB018S4-2P SINGLE ZONE MINI-SPLIT HEAT PUMP

| INDOOR SPECIFICATION | NS | | | | |
|-----------------------|--------|-----------------------------|-------------------------------|--------|-----------|
| PERFORMANCE | | DIMENSIONS | | | |
| Airflow (CFM) | High | 459 | Unit Dimensions (in) | Height | 12-3/4 |
| | Medium | 329 | | Width | 38-1/4 |
| | Low | 271 | | Depth | 9-1/8 |
| Sound Pressure (dBA) | High | 45 | Unit Net/Shipping Weight (lb) | | 25/32 |
| | Medium | 38 | PIPING | | |
| | Low | 30 | Liquid/Gas O.D. Flare (in.) | | 1/4 , 1/2 |
| ELECTRICAL DATA | | Drain Connection O.D. (in.) | | | |
| Power Supply (V/Hz/Φ) | | Supplied by ODU | - () | I | |
| Rated load amps (RLA) | | 7.50 | | | |
| Power Output (W) | | 30 | | | |

INDOOR DIMENSIONAL DRAWINGS - INCHES (MM)

