

SUBMITTAL DATA - WALL MOUNTED
MHB024S4S-1P - MWHB024S4-2P

SINGLE ZONE MINI-SPLIT HEAT PUMP

Job:	
Location:	
Schedule No.:	
System Designation:	

FEATURES

Outdoor Unit: MHB024S4S-1P

Engineer:

Architect:


Date:

For: □ Reference □ Approval □ Review □ Construction

Indoor Unit: MWHB024S4-2P



- DC Inverter Control
- Compressor Overcurrent Protection
- Defrost Control



- Auto Restart
- Three Speed Fan
- Flare Connections
- Multi-Refrigerant Outlet
- LED Readout
- Wireless Remote Included

164 (50)
82 (25)
3/8
5/8
25
0.32

PRODUCT WARRANTY

Compressor – Seven year limited warranty All other covered components - Five year limited warranty





Non-Programmable Controller (M0STAT61Q-1) Non-Programmable Controller (M0STAT120L-1) Programmable Controller (M0STAT120N-1) Hail Guard Set (M9GARD20Q-1/24M82)





NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings, and Dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.



SUBMITTAL DATA - WALL MOUNTED MHB024S4S-1P - MWHB024S4-2P

SINGLE ZONE MINI-SPLIT HEAT PUMP


OUTDOOR SPECIFICATIONS	
PERFORMANCE	
Cooling Capacity (Btu/h) ¹	24,000
EER2	9.50
SEER2	18.5
Heating Capacity (Btu/h) ¹	24,000
HSPF2	8.6
Outdoor Fan Total Air Volume (CFM)	1,765
Ambient Temperature Operating Range	
Cooling	5°F - 122°F
Heating	5°F - 86°F
ELECTRICAL DATA	
Power Supply (V/Hz/Φ)	208/230/60/1
Minimum Circuit Ampacity (A)	19
Maximum Overcurrent Protection (A)	30
Outdoor Fan Motor RLA (A)	0.76
No. of Compressors	1

GENERAL DATA		
Connection Ratio (%)		100%
Max. # of Indoor Units		1 unit
Sound Data (dBA)		60
Refrigerant type		R-410A
Factory refrigerant charge	3 lt	os. 15 oz.
DIMENSIONS		
Unit Dimensions (in)	Height	21-7/8
	Width	32-7/8
	Depth	11-1/4
Shipping Weight (lb)		105
Net Weight (lb)		98
NOTES		


1. Cooling and Heating Capacity data is rated at the following conditions:

Cooling: 80°FDB / 67°FWB Indoor, 95°FDB Outdoor Heating: 70°FDB Indoor, 47°FDB / 43°FWB Outdoor

OUTDOOR DIMENSIONAL DRAWINGS - INCHES (MM)







NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings, and Dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency. 496054 (202312) ©2023 Lennox Industries, Inc.



SUBMITTAL DATA - WALL MOUNTED MHB024S4S-1P - MWHB024S4-2P


SINGLE ZONE MINI-SPLIT HEAT PUMP

INDOOR SPECIFICATIONS		
PERFORMANCE		
Airflow (CFM)	High	546
	Medium	402
	Low	331
Sound Pressure (dBA)	High	45
	Medium	39.5
	Low	36
ELECTRICAL DATA		
Power Supply (V/Hz/Φ)		Supplied by ODU
Rated load amps (RLA)		11.2


INDOOR DIMENSIONAL DRAWINGS - INCHES (MM)

Power Output (W)

DIMENSIONS		
Unit Dimensions (in)	Height	13-1/4
	Width	42-5/8
	Depth	9-3/8
Unit Net/Shipping Weight (lb)		30/38
PIPING		
Liquid/Gas O.D. Flare (in.)		3/8 , 5/8
Drain Connection O.D. (in.)		1



58



BOTTOM VIEW