

SUBMITTAL DATA - FLOOR CONSOLE MOUNT

MFMA012S4-1P

MULTI-ZONE MINI-SPLIT HEAT PUMP

Job:	Engineer:	
Location:	Architect:	
Schedule No.:	Date:	
System Designation:	For: □Reference □Approval □Review □Construction	

FEATURES

- Pre Heat Function
- Auto Restart

- Flare Connections
- LED Readout Panel
- Refrigerant R-410A
- · Wireless Remote Controller included

Product Warranty

All covered components - Twelve year limited warranty. Product registration required.

Product registration required.			
SPECIFICATIONS			
PERFORMANCE			
Cooling Capacity ¹ (Btu/h)		12,000	
Heating Capacity ¹ (Btu/h)		12,000	
Airflow (CFM)	High	365	
	Medium	318	
	Low	248	
External Static Pressure (in. w.g.)			
Sound Pressure (dBA)	High	45	
	Medium	40	
	Low	35	
ELECTRICAL DATA			
Power Supply (V/Hz/Φ)		208-230/60/1	
Power Supply (V/Hz/Φ) Rated load amps (RLA)		208-230/60/1 1	
Rated load amps (RLA)		1	
Rated load amps (RLA) Power Output (W)	Height	1	
Rated load amps (RLA) Power Output (W) DIMENSIONS	Height Width	1 20	
Rated load amps (RLA) Power Output (W) DIMENSIONS	-	1 20 23-5/8	
Rated load amps (RLA) Power Output (W) DIMENSIONS	Width	1 20 23-5/8 27-1/2	
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in)	Width Depth	23-5/8 27-1/2 8-1/4	
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in)	Width Depth	23-5/8 27-1/2 8-1/4 1/4	
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in)	Width Depth	23-5/8 27-1/2 8-1/4 1/4 1/2	
Rated load amps (RLA) Power Output (W) DIMENSIONS Unit Dimensions (in) Liquid Pipe Connection (in) Gas Pipe Connection (in) Condensate drain connection	Width Depth	23-5/8 27-1/2 8-1/4 1/4 1/2 5/8	



OPTIONAL ACCESSORIES	
Non-Programmable Controller (M0STAT61Q-1):	
Wireless Remote Controller (M0STAT60Q-1):	1+
Programmable Controller (M0STAT64Q-1):	

NOTES

1. Cooling and Heating capacity data is rated at the following conditions:

Cooling: 80°FDB / 67°FWB Indoor, 95°FWB / 75°FDB Outdoor Heating: 70°FDB / 60°FWB Indoor, 47°FDB / 43°FWB Outdoor









SUBMITTAL DATA – FLOOR MOUNT CONSOLE MFMA012S4-1P

MULTI-ZONE MINI-SPLIT HEAT PUMP

MFMA012S4

