

ADDENDUM

507973-01 06/2019

Addendum to Installation Instructions For ML180DFE, ML180UHE, EL180UNE, EL280UHE & EL280DFE

The DOE issued new requirements for indoor blowers in gas furnaces. This requirement was put in place to reduce energy consumption and is affective July 3, 2019. The tables per model must be applied during installation in order to meet the new fan energy rating. These tables supersede any heating speed and circulation speed tables found in the instructions.

Allowable Heating Speeds ML180DFE

Model Number	Red	Yellow	Blue	Brown	Black	
045E36A	Not Allowed		Factom: Cotting			
070E36B	Not Allowed	Allowed		Allerined	NI - 4 All I	
090E48B	Allowed	Allowed	Factory Setting	Allowed	Not Allowed	
110E60C	Not Allowed					

Allowable Circulation Speeds ML180DFE

Model Number	Red	Yellow	Blue	Brown	Black	
All Models	Factory Setting	Not Allowed	Not Allowed	Not Allowed	Not Allowed	

Allowable Heating Speeds ML180UHE

Model Number	Red	Yellow	Blue	Brown	Black	
045E36A	Not Allowed	Allowed				
070E36B	Not Allowed		Factory Setting	Allowed		
090E48B	Allowed				Not Allowed	
090E60C	Allowed				Not Allowed	
110E60C	Not Allowed					
135E60D	Not Allowed			No Allowed		

Allowable Circulation Speeds ML180UHE

Model Number	Red	Yellow	Blue	Brown	Black	
All Models	Factory Setting	Not Allowed	Not Allowed	Not Allowed	Not Allowed	

Allowable Heating Speeds EL180UHNE

Model Number	Red	Yellow	Blue	Brown	Black
040NE36A		Factory Setting	Allowed		Not Allowed
060NE36A	Not Allowed	Net Allewed	Not Allowed		
080NE48C	Not Allowed	Allowed	Factory Setting	Allowed	Allowed
100NE60C					Not Allowed



Allowable Circulation Speeds EL180UHNE

Model Number	lodel Number Red		Blue	Brown	Black	
All Models	Factory Setting	Not Allowed	Not Allowed	Not Allowed	Not Allowed	

Allowable Heating Speeds EL280UHE

/ morrano moduli g opodao EEEOOTIE										
Model	Low Fire Heating Speeds						High Fi	re Heating	Speeds	
Number	Red	Yellow	Blue	Brown	Black	Red	Yellow	Blue	Brown	Black
045E36A	Factory Setting	Allowed		Allowed			Factory		Allowed	
070E36A	Factory Setting	Allowed					Setting		Allowed	
090E36B	Allowed	Factory Setting	Allowed		Not	Not	Allowed	Allowed	Factory Setting	Allowed
090E48B	Factory Setting	Allowed		Not Allowed	Allowed	Allowed	Factory Setting	Allowed	Allowed	Allowed
110E48C	Allowed	Factory Setting					Allowed		Factory Setting	
110E60C	Factory Setting	Allowed	Not Allowed				Factory Setting		Allowed	

Allowable Circulation Speeds EL280UHE

Model Number	Red Yellow Blue		Brown	Black		
045E36A	Factory Sotting	Allowed				
070E36A	Factory Setting	Allowed				
090E36B	Allowed	Factory Setting	NI-4 All	Not Allowed	NI-4 Allannad	
090E48B	Factory Setting	Allowed	Not Allowed		Not Allowed	
110E48C	Allowed	Factory Setting				
110E60C	Factory Setting	Allowed				

Allowable Heating Speeds EL280DFE

Model		Low Fir	e Heating	Speeds	High Fire Heating Speeds					
Number	Red	Yellow	Blue	Brown	Black	Red	Yellow	Blue	Brown	Black
070E36A	Factory Setting	Allowed	Not	Not	Not	Not	Factory	Allowed	Allowed	Allowed
090E48B	Factory Setting	Allowed	Allowed	Allowed	Allowed	Allowed	Setting	Allowed	Allowed	Allowed

Allowable Circulation Speeds EL280DFE

Model Number	Red	Yellow	Blue	Brown	Black
070E36A	Footony Sotting	Allowed Not Allowed	Not Allowed	Not Allowed	Not Allowed
090E48B	Factory Setting		Not Allowed	Not Allowed	