

SUBMITTAL DATA - WALL MOUNTED MHB009S4S-1L - MWHB009S4-1L

SINGLE ZONE MINI-SPLIT HEAT PUMP

Job:	Engineer:
Location:	Architect:
Schedule No.:	Date:
System Designation:	For: ☐ Reference ☐ Approval ☐ Review ☐ Construction

FEATURES

Outdoor Unit: MHB009S4S-1L



- **DC Inverter Control**
- **Compressor Overcurrent Protection**
- **Defrost Control**

Indoor Unit: MWHB009S4-1L



- **Pre-Heat Function**
- **Auto Restart**
- Three Speed Fan
- **Flare Connections**
- **Multi-Refrigerant Outlet**
- **LED Readout**
- Wireless Remote Included

PIPING	
Line Set and Elevation Guidelines	
Maximum Line Set Length ft. (m)	82 (25)
Maximum Elevation - Outdoor Unit Below/Above Indoor Unit ft. (m)	33 (10)
Liquid Line Set Diameter (in.)	1/4
Gas Line Set Diameter (in.)	3/8
Pre-Charge (ft.)	25
Additional Charge Per Ft. (oz.)	0.16

PRODUCT WARRANTY

Compressor - Seven year limited warranty All other covered components - Five year limited warranty





OPTIONAL ACCESSORIES

Non-Programmable Controller (M0STAT61Q-1) Programmable Controller (M0STAT64Q-2) Hail Guard Set (M9GARD20Q-1/24M82)






SUBMITTAL DATA - WALL MOUNTED MHB009S4S-1L - MWHB009S4-1L


SINGLE ZONE MINI-SPLIT HEAT PUMP

OUTDOOR SPECIFICATIONS					
PERFORMANCE		GENERAL DATA			
Cooling Capacity (Btu/h) ¹	9,000	Connection Ratio (%)		100%	
EER2	12.5	Max. # of Indoor Units		1 unit	
SEER2	21.5	Sound Data (dBA)		55	
Heating Capacity (Btu/h) ¹	10,000	Refrigerant type		R-410A	
HSPF2	9.1	Factory refrigerant charge	11	1 lbs. 13 oz.	
Outdoor Fan Total Air Volume (CFM)	1,294	DIMENSIONS			
Ambient Temperature Operating Range		Unit Dimensions (in)	Height	21-7/8	
Cooling	5°F - 122°F		Width	32-7/8	
Heating	5°F - 86°F		Depth	11-1/4	
ELECTRICAL DATA		Shipping Weight (lb)		64	
Power Supply (V/Hz/Φ)	115/60/1	Net Weight (lb)		58	
Minimum Circuit Ampacity (A)	20	NOTES			
Maximum Overcurrent Protection (A)	30				
Outdoor Fan Motor RLA (A)	0.4	Cooling and Heating Capacity data is rated at the following conditions:			
No. of Compressors	1	Cooling: 80°FDB / 67°FWB Indoor, 95°FDB Outdoor			
		Heating: 70°FDB Indoor, 47°FDB / 4			

OUTDOOR DIMENSIONAL DRAWINGS - INCHES (MM)



FRONT VIEW



NOTE – Due to Lennox' ongoing commitment to quality, Specifications, Ratings, and Dimensions are subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.

495978 (202305) ©2023 Lennox Industries, Inc.



SUBMITTAL DATA - WALL-MOUNTED MHB009S4S-1L - MWHB009S4-1L SINGLE ZONE MINI-SPLIT HEAT PUMP

INDOOR SPECIFICATION	NS				
PERFORMANCE			DIMENSIONS		
Airflow (CFM)	High	239	Unit Dimensions (in)	Height	11-1/2
	Medium	170		Width	28-3/4
	Low	137		Depth	8-1/8
Sound Pressure (dBA)	High	37.5	Unit Net/Shipping Weight (lb)		18/23
	Medium	28	PIPING		
	Low	20	Liquid/Gas O.D. Flare (in.)		1/4 , 3/8
ELECTRICAL DATA			Drain Connection O.D. (in.)		1
Power Supply (V/Hz/Φ)		Supplied by ODU	- ,	'	
Rated load amps (RLA)		6.3			
Power Output (W)		20			

